

COOLMED

# CoolMed 145L Medium Glass Door Refrigerator

Model: CMG125

## Overview

- +2°C to +8°C temperature range
- Core temperature display represented by air temperature probe
- External digital controller and temperature display
- Battery back up (for controller)
- Fitted lock with 2 keys



**5 YEARS PARTS & LABOUR WARRANTY**

## Key Features




### Controller

Controller system. Read, record, reset with the touch of one button. Adjustable temperature setting.



### Battery back up

Should there ever be a power outage the battery backup will continue to monitor the internal temperature of the fridge.



### Porthole

Factory fitted porthole enables quick and easy access for any secondary temperature monitoring probes.



### LED lighting

Low voltage LED lighting improves running cost as no heat is produced. Long lasting.



### Flexible storage

Multiple shelf locations. Back stop on every shelf provides a flexible storage solution.

## Details

Model: CMG125

<b>Gross Capacity (litres)</b>	148
<b>Net Capacity (litres)</b>	145
<b>Unit External Width (mm)</b>	595
<b>Unit External Depth (mm)</b>	595
<b>Unit External Height (mm)</b>	815
<b>Product Weight (kg)</b>	44
<b>Packed Width (mm)</b>	650
<b>Packed Depth (mm)</b>	650
<b>Packed Height (mm)</b>	865
<b>Packed Weight (kg)</b>	47
<b>Temperature Range</b>	+2°C to +8°C
<b>External Finish, Internal Finish</b>	Painted Steel, Painted Steel
<b>Battery Back Up</b>	Yes (for controller)
<b>Door Finish, Door Type, Door Style</b>	Painted Steel, Glass, Hinged, Right Hand
<b>Open Door Sensor</b>	Yes
<b>Lock</b>	Yes
<b>Adjustable Feet (number)</b>	Yes (2)
<b>Porthole</b>	Yes
<b>Porthole Location</b>	Rear, Middle
<b>Temperature Display on Panel, Temperature Alarm, Remote Alarm Contacts, Audible Alarms, Visual Alarms</b>	Yes

<b>Number of Shelves</b>	4 (2 full size, 1 small base shelf)
<b>Number of Shelf Positions</b>	6
<b>Shelf Material</b>	Plastic Coated Wire
<b>Interior Light</b>	Yes
<b>Light Type</b>	LED
<b>Light Activation</b>	Switch
<b>Fan</b>	Yes
<b>Spark Free</b>	No
<b>Controller Type</b>	Digital, External
<b>Number of Probes</b>	2
<b>Probe Type</b>	Air
<b>Ambient Temperature Range</b>	+10°C to +30°C
<b>Refrigerment Type</b>	R600a
<b>CFC Free, HCFC Free, Ammonia Free</b>	Yes
<b>Voltage Supply</b>	220-240V/ 50Hz
<b>Certification</b>	CE/UK
<b>Noise Level (dBA)</b>	50
<b>Input Power (W)</b>	76
<b>Cable Length (cm)</b>	20
<b>Energy Consumption (kWh/annum)</b>	0.9